



High Performance Concrete with Fiber Reinforcement

Bill Lyons FACI

National Business Development Group Northeast Region 201-401-3391 wlyons@euclidchemical.com




Presentation Outline


- Concrete Cracking
- Concrete Shrinkage
- Fiber Reinforced Concrete
- Design and Specification
- Applications
- ACI 544.4R-18












Dry heat and windy conditions caused widespread cracking

Theories of Shrinkage



- ACI 223 graphic
- curves dependent on many factors
- no influence from fibers

- importance of curing illustrated
- mix design can influence
- testing diligence is very important

Improving durability of concrete

- > Making the concrete denser and less permeable
 - Lower w/c, use SCM, proper gradation, curing …
- Minimizing cracking potential
 - > ...low shrinkage concrete
- Controlling the cracks / crack widths
 - ➤ ... fiber reinforcement



Fiber reinforcement

- Fibers are used in concrete for the same reason that straws were used in mud bricks thousands of years ago: **post-crack strength**.
- Structural fibers provide additional tensile and flexural capacity. (not compressive)





How to Differentiate the Fiber Types –

micros & macros

- In general, the "industry" has accepted that steel macro-fibers and "older" micro-synthetic fibers (fibrillated, monofils, etc) are not used under the same conditions.
- Micro-synthetics "secondary" reinforcement; plastic shrinkage only
- Steel fibers industrial floor design; replacement of heavier reinforcing configurations
- Synthetic macro-fibers can be thought of like steel fibers, but simply not made of steel. The physical characteristics of these fibers (length, tensile strength, diameter, etc.) are all different, when compared to traditional micro-synthetics.
- Dosages of macro-fibers should be calculated by engineering requirements.



Typical Fiber Types & Dosage Rates

Micro-Synthetic Fibers

monofilament polypropylene and other synthetic materials
 0.5 to 1.5 pcy for control of plastic shrinkage cracking only

Micro-Synthetic Fibers

• fibrillated polypropylene

1.0 to 1.5 pcy for control of plastic shrinkage and some temperature and shrinkage cracking as a replacement for very light WWM

Macro-Synthetic Fibers

monofilament polypropylene and other synthetic materials

3.0 to 10 pcy for temperature and shrinkage cracking control and limited structural reinforcement – highly engineered calculations

Steel Fibers

deformed geometry drawn steel wires


15 to 100 pcy for temperature and shrinkage cracking control and limited structural reinforcement – highly engineered calculations

During the construction

- Reduced labor and costs
- Reduced construction time
- Increased safety
- Potential reduction in thickness

After the construction (in service)

- Three dimensional reinforcement
- Shorter and thinner cracks (if any)
- Less spalling and chipping
- Increase in long-term durability





Performance and Specifications



• Not all fibers are created equal!

Calculated fiber dosages are becoming more prevalent in the specification community and will 'force' manufacturers to provide test data and documentation that a specific fiber type is suited for the application.

fiber alternate shall be macro-fiber (steel or synthetic) complying with ASTM C1116 and provide equivalent tensile and/or bending resistance to # 4 rebar (Grade 60) placed 2" from top of a 6" slab or mid-depth in a 8" wall......

and / or


- "A minimum fe3 of 200 psi
- Approved dosage rate shall satisfy the performance requirements".

- Not all fibers are the same, that is why it is important to specify fibers based on their "performance" in "fiberreinforced concrete (FRC)".
- Parameters related to the residual strength of FRC (R_{e,3} and f_{e,3}) can be used for specifications. The values depend on the design and specifics of the project.



ASTM C 1609 ????

Effect of Fiber Dosage



Mid-Span Net Deflection, in

TSSF	f _r (psi)	f _{e3} (psi)	R _{e3} (%)
3 рсу	597±43	133±9	22±3
5 ру	669±9	209±15	31±2
7.5 рсу	651±25	293±29	45±4
10 рсу	662±8	372±39	56±6



The majority of floors in FedEx Ground distribution centers have fiber-reinforcement.

- C. Macro Synthetic Fiber: As shown on drawings, macro synthetic fiber reinforcement shall be used for the purpose of controlling temperature and drying shrinkage cracking. Macro-synthetic fibers are not intended, nor shall be permitted, to replace structural reinforcing steel required by design without FXG review and approval. Micro-synthetic fibers and cellulose fibers shall not be permitted. Macro Synthetic Fiber shall meet the following criteria:
 - Type: Fiber shall meet the requirements of ASTM C1116 for Type III Synthetic Fibers
 - 2. Length: Fiber length shall measure 1¹/₂" 2".
 - Post Crack Residual Strength: Fiber shall provide a minimum post-crack residual strength value (fe3) of 200 PSI when measured in accordance with ASTM C1609. Fiber manufacturer shall provide data in accordance with this requirement.
 - Tensile Strength: Fiber shall provide a minimum tensile strength of 70 KSI when tested in accordance with ASTM D2256
 - Modulus of Elasticity: Fiber shall provide a minimum modulus of elasticity of 1200 KSI when tested in accordance with EN 14889
 - 6. Aspect Ratio: Fiber shall provide an aspect ratio of 70 90

DOT Fiber Specification

Standard Guidelines for Product Review Synthetic Blended Fiber Reinforcing; Section 02045.30 April, 2014

Oregon

DEPARTMENT OF TRANSPORTATION Construction Section 800 Airport Road SE Salem, OR 97301-4798 503/986-3059

02045.30 - Synthetic Blended Fiber Reinforcing

<u>General</u> – Synthetic Blended Fiber Reinforcing submitted under this category will be used in HPC Bridge Decks and SFC Overlays as shown on the plans or specifications.

Test a currently approved ODOT HPC 4000- ³/₄" and SFC(MC) 3000- ¹/₂" mix design in accordance with the latest version of ASTM C1579. Test sample materials shall be obtained from Knife River in Central Point, Oregon. Test samples shall use the constituents currently used at the plant, i.e. cement, fly ash, silica, agg., admixtures, etc.

Test a currently approved ODOT HPC 4000- ³/^a and SFC(MC) 3000- ¹/₂^a mix design in accordance with the latest version of ASTM C1399. HPC and SFC test samples shall be obtained from Knife River in Central Point, Oregon. HPC and SFC test samples shall use the constituents currently used at the plant, i.e. cement, fly ash, silica, agg., water, admixtures, etc.

Fiber dosage rates developed for QPL inclusion will be noted in the QPL listing remarks section and used for production on ODOT projects which specify fiber reinforcing.

Specifications:

- 1. ASTM C1116, Section 4.1.3, Type III Synthetic, Polyolefin Fibers.
- ASTM C1579 Plastic Shrinkage Cracking of Restrained Fiber Reinforced Concrete: Report results for manufacturers recommended dosage rates. Minimum reduction > or = 85%.
- ASTM C1399 Average Residual Strength of Fiber Reinforced Concrete: Report results for manufacturers recommended dosage rates. Minimum residual strength > or = 195 psi.

To apply for inclusion on the QPL, submit the following:

Colorado DOT

February 18, 2016

REVISION OF SECTION 601 FIBER-REINFORCED CONCRETE

Section 601of the Standard Specifications is hereby revised for this project as follows:

Subsection 601.03 shall include the following:

Where Fiber-Reinforced Concrete is specified or designated in the plans, the concrete mix shall include approved polyolefin fibers. Unless otherwise specified, a minimum of 3.5 pounds per cubic yard of polyolefin fiber reinforcement shall be evenly distributed into the mix. Mixing shall be as recommended by the manufacturer such that the fibers do not ball up. Polyolefin fibers shall meet the requirements of ASTM C1116 and ASTM D7508.

Where Macro Fiber-Reinforced Concrete is specified or designated in the plans, the concrete mix shall include approved macro polyolefin fibers. A minimum of 4.0 pounds per cubic yard of macro polyolefin fiber reinforcement shall be evenly distributed into the mix. If less than 4.0 pounds per cubic yard of macro polyolefin fiber reinforcement is used in the mix, the Contractor shall provide test results showing the mix design has a residual strength of 170 psi as determined by ASTM C1609. Mixing shall be as recommended by the manufacturer such that the fibers do not ball up. Macro polyolefin fibers shall meet the requirements of ASTM C1116 and ASTM D7508 with the following exceptions:

(1) Tensile strength shall be a minimum of 65 ksi

- Modulus of Elasticity shall be a minimum of 1,000 ksi
 Cut length shall be 1.5 to 2.2 inches
- (4) Aspect Ratio shall be 50 to 100

Subsection 601.05 shall include the following:





NORTH

Performance Whitetoppings

DOT initiatives, specification

- DOT's are increasingly looking at fiber concrete to use in whitetoppings and pavement construction to extend service life
- IL, IN, UT (decks); coming to OH, KY
- QPL driven, minimum performance requirements – ie: Re₃> 20%
- Large order projects, highly competitive
- Fibers ideally suited for finishing





INDOT SR 9 FIBER REINFORCED CONCRETE PAVEMENT

- 6 miles (10 km) of pavement was completed in 2017
- Requiring 14,000 yd³ (10,700 m³) of concrete
- Dosage 4 lbs/yd³ (2.4 kg/m³)
- Performance based specification
- Concrete was jointed at 6 ft. (1.8 m)





CR44 Bridge Deck Overlay Hinckley Ohio



CR44 BRIDGE DECK OVERLAY

- High Performance Modified
 Concrete Mixture
- Research project through ODOT & University of Akron
- 130 yd³ of concrete
- Increase durability and service life through reduction of cracking



Hart in a printing of a	And the second second	A State
Martin and a star	and the second second	- Michiel
A ARA DES	- Children (Children (Chil	Anisother Pro-
the hard and the second second		
4 31 1 5th 2		12173535
ALL COMPANY STATE	and the second second	200.月六小
& Alleine state	- (2.13 AL39)	1999
16-1-1-1 C # 7 70	- ANTIN CARE AN	60.00
Million to safe	and the second	18.8-1
2:000-1970.00	A	WERE NO.
the stand to mine	" Zahit date	Citrari
E. Martin	N.W. ST	All Court
12 2 Store and		LOV IN THE
(Participation)	1001000	Contractor of the
The second	1 1.255 1	CIT shew
New Contraction of the Contracti	1 Carting	AM AND -
HEALING &	1 Maintains a	- Carlos I
and he had a set	LIP SERVICE	
ARE ALTERNAL AS	1 - DENEMON	
A STATE OF STATE		and the second

BLACK OAK CASINO RV PARK (CA)

- 6 inch concrete pavement for RV parking
- Total area 206,400 ft2 (19,174 m2)








Fibers for Composite Metal Decks (CMD)

CODE Approved

Steel Deck Institute (SDI C-1.0.) allows for using macro fibers in composite metal deck to replace wire mesh. This language is included in the IBC 2015.



Reinforcement:


a. Temperature and shrinkage reinforcement, consisting of welded wire fabric or reinforcing bars, shall have a minimum area of 0.00075 times the area of the concrete above the deck (per foot or meter of width), but shall not be less that the area provided by 6 x 6 – W1.4 x W1.4 welded wire fabric.

Fibers shall be permitted as a suitable alternative to the welded wire fabric specified for temperature and shrinkage reinforcement. Cold-drawn steel fibers meeting the criteria of ASTM A820, at a minimum addition rate of 25 lb/cu yd (14.8 kg/cu meter), or macro synthetic fibers "Coarse fibers" (per ASTM Subcommittee C09.42), made from virgin polyolefin, shall have an equivalent diameter between 0.4 mm (0.016 in.) and 1.25 mm (0.05 in.), having a minimum aspect ratio (length/equivalent diameter) of 50, at a minimum addition rate of 4 lb./cu yd (2.4 kg/m³ are suitable to be used as minimum temperature and shrinkage reinforcement.



Fibers for deck construction

- Steel decking acts as stay-in-place formwork, carries and distributes loads to joists and columns
- Concrete placement provides a level wearing surface and rigid mass to structure
- Reinforcement in concrete can be in different forms depending on design and function








IBC 2015 permits fiber for temp / shrinkage steel replacement on c-m-d projects

- Some projects require UL/ULC report on fire resistance (2 hour fire rating).
- Light-medium gauge mesh can be replaced with macro-fibers (synthetic or steel).
- Heavier mesh or rebar conversion may lead to a higher dosage for









Precast Products

Crack control, engineered design





Burial Vaults and Septic Tanks

Steel fibers used in tunnel lining segmental units.



Multiple applications

Individual requirements

- Significant decrease in production cycle time
- Reduced labor costs
- Reduction in breakage and repair costs
- Elimination of the potential for corrosion
 - Crack prevention
 - Increased ductility
 - Impact resistance
 - Less spalling















Tools and Resources

NESMEA

Eastern States' Materials Engineers Association

- Engineered Design Guides
- Fiber Software Program
- Phone Calculator App

Chapter 1 Introduction to Fibers and Fiber Reinforcement


1.1	History and Development
1.2	Types of Fibers
1.3	Basics of Fiber Reinforcement
1.4	Cracking Phenomenon
1.5	FRC Benefits During Construction
1.6	FRC Benefits in Service
1.7	Economic and Environmental Benefits

Chapter 2 FRC Properties and Design Methods

2.1	FRC Characteristics
2.2	FRC Test Methods
2.3	Design Considerations for FRC
2.4	Design Concept for Conventional Reinforced Concrete
2.5	Design Concept for Conventional Reinforced Concrete (2 mats)
2.6	Design Concept for FRC
2.7	Design Concept for Hybrid Reinforcement (Rebar+fibers)
2.8	Design for Shrinkage/Temperature Crack Control
2.9	Moment Calculation and Design for a Suspended Section
2.10	Moment Calculation and Design for a Supported Section
2.11	Design Tools by Euclid Chemical
2.12	Design Codes, Guides, and Recommendations

3.1	Slab-on-Grade (Based on ACI 360)	
3.2	Composite Steel Decks (Based on SDI)	
3.3	Precast Units	
3.4	Residential Foundation Walls	
3.5	Shotcrete	
3.6	Decorative Concrete	
3.7	Other Subjects: Control Joints and Load Transfer	
3.8	Other Subjects: Low Shrinkage FRC Slabs	
	ter 4 Practice Recommendation	
FRCF	Practice Recommendation	
FRC F 4.1	Practice Recommendation Adding and Mixing Fibers (For ready mix producers)	
FRCF	Practice Recommendation Adding and Mixing Fibers (For ready mix producers)	
4.1 4.2 4.3	Practice Recommendation Adding and Mixing Fibers (For ready mix producers) Placing and Finishing FRC (For concrete contractors)	

uclid Chemical	1									
Loading Zone 1	Save Loading Zo	ne	Find Do	sage	Convert to SI	Conver	rt to Imp	Delete Loading Zone		
Comon Lood I	Name: Loadin	g Zone	1							
Add Loading Zone	Compressive St	rength	[F _c]:				Thick	kness of Slab [t]:		
Add Uniform Load	4,000	psi	٠		atic Load	1.2	10.0		ĩn ▼	
Add Line Load	Ultimate Flexura	Stren	gth [F _r]				Colu	mn Spacing:		
Add Lift Truck Load	570	psi	٠	-	namic Load	1.4	50.0		ft 🔻	
Add Vehicle Load	Modulus of Elast	icity IE	1.				Cont	raction Joint Spacing:		
Add Rack Post Load	3,579,879						25.0		ît 👻	
	5,575,675	psi					23.0		R •	
	Subgrade Modul	us (k):					Temp	perature Difference:		
q (weight/area)	175	pci	•	-			9.0		F 🕶	
++++	Friction Coefficie	ent:		Po	ur Conditions:		Conc	crete Shrinkage Strain:	0.0004	٠
+ + +	1.30			0	Interior		Aver	age Relative Humidity (RH) L	.evel:	
	Granular Subba	ise	•	C	Exterior		RH > 8	0% 65% 50% Typical Outdoor	35% Typical Indoor	RI
	Save Uniform Lo	ad	Delete (Iniform	Load					



Bar diameter has a "drop down" menu with common options for size

Bar spacing should contain the lowest numerical value; example: 6" x 12" – enter 6

Steel strength "drop down" menu has three options; wire is typically 70 ksi, rebar is 60 ksi

For a quick calculation of fiber dosage, without a report, select the button

QUICK CALCULATION ()

ASTM and ACI Approvals

ACI and ASTM do not endorse, certify or prohibit the use of materials – there is no "approved by ACI" type of language in any specification.

Design of Slabs on Grade ACI 360 CHAPTER 11

11.2.2 Design Principles Macro synthetic fibers provide increased post-cracking residual strength to concrete slabs-on-ground. The same principles for steel in section 11.3.3 can be used for macro synthetic fibers.

ACI 360 (Slab on Grade) is undergoing a revision that will include macro-fibers and extended joint possibilities

ASTM Standards for Fiber

- **C1116** Standard Specification for Fiber-Reinforced Concrete and Shotcrete
- **D7508** Polyolefin Chopped Strands for use in Concrete
- **C1609** Flexural Toughness (Beams)
- **C1399** Average Residual Strength
- **C1550** Flexural Toughness (Round Panels)
- C1579 Plastic Shrinkage

+ additional testing on abrasion, fatigue, creep, durability, stength, etc.



Chopped Strands Attributes	Micro Chopped Strands	Macro Chopped Strands	Hybrids Chopped Strands
Compliance with Specification C1116/C1116M, Type III	Required	Required	Required
Denier	580 or less	581 or greater	As Designated – Must be stated
Finish Content	1.5 % max	1 % max	1.5 % max on Micro Portion 1 % max on Macro Portion
Tensile Strength	N/A	Greater than 344.4 MPa [50 000 psi]	Micro Portion (N/A) Macro Portion – Greater than 344.4 MPa [50 000 psi]
Cut Length	3 – 50 mm	12 – 65 mm	As Designated - Must be stated

TABLE 1 Conformance Requirements for Chopped Strands for Use in Concrete

A wealth of information on fibers...

- 544.1R Fiber-Reinforced Concrete
- 544.2R Measurement of Properties of Fiber-Reinforced Concrete
- 544.3R Guide for specifying, proportioning, mixing, placing, and finishing FRC
- 544.4R Guide to Design with Fiber-Reinforced Concrete
- 544.5R Report on the Physical Properties and Durability of Fiber-Reinforced Concrete
- 544.7R Report on Design and Construction of Fiber-Reinforced Precast Concrete Tunnel Segments
- 544.8R Report on Indirect Method to Obtain Stress-Strain Response of Fiber-Reinforced Concrete
- 544.9RReport on Measuring Mechanical Properties of Hardened Fiber-Reinforced Concrete546.9RContraction of Measuring Mechanical Properties of Hardened Fiber-Reinforced Concrete
- 506R Guide to Shotcrete
- 506.1R State-of-the-art report on Fiber-Reinforced Shotcrete
- **506.2** Specification for Shotcrete
- 440R State-of-the-art report on Fiber-Reinforced Plastic (FRP)
- **302.1R** Guide for concrete floor and slab construction
- **325.10R** State-of-the-art report on roller compacted concrete pavement
- 207.5R Roller compacted mass concrete
- **330R** Guide for design and construction of concrete parking lots
- **330.1** Standard specification for plain concrete parking lot
- **332.1R** Guide to Residential Concrete Construction
- **360R** Design of slabs-on-grade
- **116R** Cement and concrete terminology



An overview of ACI 544.4R-18 Design Guide for Fiber Reinforced Concrete

October, 2018

ACI 544 – Fiber Reinforced Concrete

Committee Mission: Develop and report information on concrete reinforced with short, discontinuous, randomly-dispersed fibers.

Goals: Develop new documents, revise and update the existing documents to reflect the significant changes in the fiber reinforced concrete development, use, and applications.

Chair: Liberato Ferrara



7 active subcommittees

- 544-0A FRC-Education Production Application
- 544-0C FRC-Testing
- 544-0D FRC-Structural Uses
- 544-0E FRC-Mechanical Properties
- 544-0F FRC-Durability
- 544-0L Liaison Subcommittee
- 544-SC FRC-Steering Committee

ACI 544.4R

In need of a tune-up


- Previous version 30 years old
- Based on steel fiber research and design
- No information on macro-synthetics
- Focused on mechanical properties and design applications

				ACI 544.4R-8 (Reapproved 200)
Design Cons	siderations	for Steel Fib	er Reinfor	ced Concrete
		ed by ACI Commit	ee 544	
Seads Claim			Jame 1. Dami	
search H Aband	-	Group C.B.et	Secretary	
M. Artchinian P. X. Balagura		Name M State		Rabb C. Robinson
Caire Ball		Rep 1 Tabl		E & Ichrole* Munit Schepelt*
Name P Ball, 5 Gottes B. Beneri		Collin D. Hilberton Clarke: W. Southi		Field Semanni
Atres Berley		Detd & Looked		A D. Speciation
John T Chiefr		Boy 34 Mago		X. N. Detary Pow C. Tetrall
JOBTON Z. Chirpad?"		Heary N. Silvesh, het Anit Malmood		B L Tites
Sidney Readown Robert 2 Octor		Nelsia C. Medal		George J. Union
Malves A Gallage		Repy 7 Maller		Guy L Venders
Values Gepalateres		D. R. Margas A. E. Namura		Matta Washington Salitati Kalitati Salitati Kalitati Salitati Sali
Antonio Jose Guarra Liced Z. Husimur		Tenley L. Peul"		C. E. Wilson
M. Natio Smooth		Set 1. Perine		Souid 2 Wetkele
		Constant Party and Party a		
Carlo E Barge Is ² To presenting of londspoor of the front series and more using the f provide an definition of the provided optimizer on load	the province for the	T. Reministers D. T. Saldy Web- Chapter 3-6 ment 3-6546 Spini 3-74ees in 1	Vesige application	George Y. Wi Rober C. Zaller Resaid F. Zaller
Carlo 2 Barge 2:* The presentant of level sprant of the front concert and matter using the ly properties are downed in a second	tign practice for the fort it minuted black it my presented and (T. Annicians D.Y. Tady Mark Chapter 3-4 mmil 3340h 13-50ar a he 3-60ar a he 3-60ar a he 3-60ar a he 3-60ar a he 3-60ar a he	-	George Y. Wi Rober C. Zaller Resaid F. Zaller
Carlo & Barge Lr. The present time of development of the first concress on instruming the fi- properties are distanted, sharp method applications to band forwards from instruction on time match, forwards development, the mat- match, forwards development, the mat- tion of the standard development.	City partice for the for a manual labor is an provided and a struct manual law, menor basedab, and	T Annicitans D Y. Taldy Mith. Chapter 3-4 Diff. J.Manu II J.S.Manu J.S.Manu II	ning pinting	Geogra Y To Lifee C Silan Amail 7 Dala 19, p. 544.4R.4
Cashe & Bange Lo The present time of development of the first concress on instruming the fi- properties are descended, sharp method uplications are limited forwards from instruction on time on proving instruments (instrume on proving instruments) (instrume instruments), instruments (instruments) (instruments), instruments), instruments (instruments), instruments), instruments (instruments), instruments), instruments (instruments), instruments), instruments), instruments (instruments), instruments), instruments), instruments), instruments (instruments), instruments), ins	City partice for the for a manual later is an provided and a struct manual later memory manual, and	T. Randicham D. Y. Lady Chapter 3-4 Droft 20-Stars in 10-Stars in	nin pintin terences, p. 544,4	Geogra Y To Labor Calan Annal F Dalo M, p. SALAR-8
Carlor & Banges Le* The present state of development of his properties are distanted, sharp meller applications are shared applications are shared to be a state of the state of the state and the state of the state of the state CONTENTS Theapter 1 Astronological, 5.544	Con province for the Decision environment March in our presented and a minute memory. Decision memory installed and second memory. Decision memory installed and second se	T. Annichians D. Y. Tady and J. Mish J. Mish J. Mish J. Mish J. Mish J. Mish J. Mish J. Mish Mark J. Mish Mark J. Mish Mish Mish J. Mish Mish Mish Mish Mish Mish Mish Mish	nice pinties ferences, p. 544,4	Geogra Y To Labor Calan Annal F Dalo M, p. SALAR-8
Castle & Bauges Is* The present state of development of the forest courses and meter using and properties are discard, design nervice opplications are stated thereads have beameds laws and thereads have beameds laws and thereads have beameds laws and thereads are beamed laws and thereads are beamed laws and thereads are beamed laws are provided and the CONTENTS Nappler 1 development and happing to 5.644 do 3	Con province for the Decision environment March in our presented and a minute memory. Decision memory installed and second memory. Decision memory installed and second se	T. Randicham D. Y. Lady Chapter 3-4 Droft 20-Stars in 10-Stars in	nice pinties ferences, p. 544,4	Geogra Y To Labor Calan Annal F Dalo M, p. SALAR-8
Carlo & Barge Lr* The present state of development of the properties are development of the properties are developments applications on band Knowle from instantial states on much instantian instantial in the much instantian instantial in the CONTENTS Properties of the states of the Properties of the states of the states of the Properties of the states of the states of the Properties of the states of the states of the states of the Properties of the states of the s	Con province for the Decision environment March in our presented and a minute memory. Decision memory installed and second memory. Decision memory installed and second se	T. Randcham D. Y. Taday and D. Y. Taday D. Y. Taday D. S. Tanana J. J. S. Tanana J. S. S. Tanana J. S. S. Tanana J. S. S. Tanana J. S. S. S	venn mine pôintine ferences, p. 544,4 tr Norman Sci wings m	Geogra Y To Lifee C Silen Annal F John 19, p. Statura 19, p. Statu
Carlo E Barge, 1: The present state of development of the properties over similar that the state of the properties over similar deplements over similar deplements over similar deplements are similar the state of the similar maps into the similar of the similar maps into the similar of the similar deplement over similar CONTENTS Contents States of the similar States of the similar similar States of the similar States	Con province for the Decision environment March in our presented and a minute memory. Decision memory installed and second memory. Decision memory installed and second se	T. Randcham D. Y. Taday and D. Y. Taday D. Y. Taday D. S. Tanana J. J. S. Tanana J. S. S. Tanana J. S. S. Tanana J. S. S. Tanana J. S. S. S	nice pinties ferences, p. 544,4	Geogra Y To Lifee C Silen Amail 7 July 19, p. 544.4R.4 19, 544.4R.4 19, 544.4R.4
Carlo E Barge Lo The present time of development of M properties are distincted using their properties are distincted using their properties are distincted using their properties are distincted and their mage, however, and their are constrained and their a	Con province for the Decision environment March in our presented and a minute memory. Decision memory installed and second memory. Decision memory installed and second se	T. Randelsam D. T. Taday Anno- Chapter 3-4 Jordan Jordan Jordan Johan Jordan Johan May Johanna Jal Sharan Ja Sharan	enni mice piloritose forences, p. 544.4 to miceanided release mice states states	Gauga Y To Labor C Jalan Ronal F Jalo H, p. SALARA RFA R
Carlo & Barge, L+ The present stars of development of the freed concress of investor using stars/ properties are distanted, design while the stars of the stars of the stars the stars of the stars of the stars the CONTENTS CONTENTS CONTENTS Apple: 1 Astronolouslos, p. 544 Anaple: 2 Allechanical properties using the Star B-2 11 Anaple 12 Anaples 13 Anaples 14 Ana	Con province for the Decision environment March in our presented and a minute memory. Decision memory installed and second memory. Decision memory installed and second se	 Remicision Y. Taday Y. Tada	Arrences, p. 544.4 Arrences, p. 544.4 Maranaa Maranaa Maranaa Maranaa Maranaa Maranaa Maranaa	Geogra Y To Lifer C Salan Annal F Sala M, p. Sållaft å
Carlo & Bange, L+ The present stars of development of the properties over some stars using stars's properties over Stard deplement are stand deplement are stard deplement are stars deplement are stars deplement are stars contenties map, insuring stars and then and, insuring stars CONTENTS Datafort 1 deproduction, p. 544. Anapter 1 deproduction, p. 544. Anapter 2 deplement 21-depression 32-depression 33-de	Con province for the Decision environment March in our presented and a minute memory. Decision memory installed and second memory. Decision memory installed and second se	T. Randelsam D. Y. Jady Nature (Chapter 3-4 Deal) (2) Chapter 3-4 Deal) (2) Chapter 3-4 Deal) (2) Chapter 3-4 Chapter 5-Not Chapter 5-Not Chapter 5-Not Chapter 5-Not Chapter 5-Not Chapter 5-Not	Annual Status Principal Annual Status Million, p. 544.487.5 PTER 1-INTROL Million Annual Status	Gauga Y To Laber C Jalan Road F Jala N, p. SALARA RIAA RIAA RIAA So DUCTION SFRC) and montor
Carlor & Bange, L+ The present stars of development of the properties concess and most using stars properties one distanced, along method opportunities one shares of the stars of the stars of the star mage, insurant stars starting, and then apply the starting starting and then apply the starting starting and then apply the starting starting and the starting starting starting at the starting	Con province for the Decision environment March in our presented and a minute memory. Decision memory installed and second memory. Decision memory installed and second se	 Remdenians V. Lady Chapter 3-4 med 23/Bah D. V. Lady D. V. La	was plinting plinting to reasonable decay man sition, p. 544.47.5 PTER 1-INTRO informatic concretes (mile concretes (mile concretes)	George Y To Lafee C Salen Annail 7 July Nr. p. SALAR-8 R-64 Sec DUCTION SFRC) and montar sectors
Carlo & Bange, Is* The present stars of development of the properties over some stars using stars's properties over stars's properties over stars's deplement area impacted, and then any, hand the stars's start of the map, hand the start of the star map, hand the start of the star map, hand the start of the star contentral CONTENTS CONTENTS Contents C	Con province for the Decision environment March in our presented and a minute memory. Decision memory installed and second memory. Decision memory installed and second se	T. Randicians D. T. Taday Anno- Chapter 3-4 Joliah J. S. Chapter 3-4 Joliah J. S. Chapter 3-4 Joliah J. S. Chapter 3-4 S. Chapter 3-Most Chapter 5-Most Chapter 5-Most Chap	Annual priorition priorition Arrendes, p. 544.4 annual annual an annual annual annu	Gauge Y To Laber C Jalen Anad F Jalo N, p. 544.4R-8 R-54. Sec 7 DUCTION SFRC and monther containing fine or while:containes
Carlo & Bange, Is* The present stars of development of the properties over some stars using stars's properties over stars's properties over stars's deplement area impacted, and then any, hand the stars's start of the map, hand the start of the star map, hand the start of the star map, hand the start of the star contentral CONTENTS CONTENTS Contents C	Constraints for figures of the second	T. Randicians D. T. Taday Anno- Chapter 3-4 Joliah J. S. Chapter 3-4 Joliah J. S. Chapter 3-4 Joliah J. S. Chapter 3-4 S. Chapter 3-Most Chapter 5-Most Chapter 5-Most Chap	Annual priorition priorition Arrendes, p. 544.4 annual annual an annual annual annu	Gauge Y To Laber C Jalen Anad F Jalo N, p. 544.4R-8 R-54. Sec 7 DUCTION SFRC and monther containing fine or while:containes
Carlo & Barge Lo The present stars of development of the properties are distanted, sharp mini- properties are distanted, sharp mini- properties are started. Knowske frame insured instante in much, Insuranter Analysis, and Bars- man, Insuranter Analysis, and Bars- man, Insuranter Analysis, and Bars- ing, Satt Ale- 20 CONTENTS CONTENTS CONTENTS Contention of the 1-4 America Starter of the 1-4 America Start	CITI practice for file fors a monoid black in our presents and in othere reserves. Due, and the second second second days a second second second second days a second second second second days a second second second second second days a second second second second second second second second second days a second seco	T. Randicians D. T. Taday Anno- Chapter 3-4 Joliah J. S. Chapter 3-4 Joliah J. S. Chapter 3-4 Joliah J. S. Chapter 3-4 S. Chapter 3-Most Chapter 5-Most Chapter 5-Most Chap	Annual priorition priorition Arrendes, p. 544.4 annual annual an annual annual annu	George Y To Lafee C Salen Annail 7 July Nr. p. SALAR-8 R-64 Sec DUCTION SFRC) and montar sectors
Carlo E Barge L* The present stars of development of the properties over distanced a design nervice opplications are distanced a design nervice opplications are distanced as the nervice stars beginning a second of the nervice stars beginning and these ages. Investment starshow, and these ages. CONTENTS CONTENTS CONTENTS Contents and 24-Comparison 24-C	City practice for the fort it moved lack it no present and invest senses. Day, moves present and direct senses. Day, moves present and direct senses.	T. Randicians D. T. Taday Anno- Chapter 3-4 Joliah J. S. Chapter 3-4 Joliah J. S. Chapter 3-4 Joliah J. S. Chapter 3-4 S. Chapter 3-Most Chapter 5-Most Chapter 5-Most Chap	Annual priorition priorition Arrendes, p. 544.4 annual annual an annual annual annu	Gauge Y To Laber C Jalen Anad F Jalo N, p. 544.4R-8 R-54. Sec 7 DUCTION SFRC and monther containing fine or while:containes
Carlo & Barge, 1x* The present stars of development of the properties over development of the properties over developments of the properties over developments of the new properties of the second stars and the second stars of the second sequel, interview developments and, interview developments (second stars), and then apply the second stars of the sequel, interview developments (second stars), and then apply the second stars of the second stars of the second stars 31 Assession 34 Assession stars and the 34 Assession stars are second as 34 Assession stars are second as 34 Assessions are second as 34 Assessions are second as 34 Assessions are second as 34 Assessions are second as 35 Assessions are second as 36 Assessions are second as 37 Assessions are second as 38 Assessions are second as 39 Assessions are second as 30	City practice for file for a monet and lack in our present and in merce senses. Day, were present and in array present and array present array present and a present and a present ar	T. Randiciam D. T. Taday Anno. D. T. Taday D. T. Ta	Annual priorition Arrences, p. 544.4 to reconstruct of other man and PTER 1-MTROI afform p. 544.4R.15 PTER 1-MTROI afformation of concerning of the afformation of the second sec	Gauge Y To Sales C Sales Anad F Sale H, p. SALARA RAA RAA W T DUCTION SFRC) and monthe continue files or sale report These a fire types of ap-
Canter & Banges Le* The present state of development of the first concress on instruming stars' properties are distanted, design which applications are itself. Reveals from instruction instruments are prepare to assessed in the set are present to assessed in the set are present to assessed in the set are CONTENTS Respect 1 - Astronolouoloor, p. 544 Respect 1 - Astrono	City practice for the Next is minuted black in my presented and it was minuted memory based of the second second second second second second second second second with second sec	T. Randiciam D. T. Taday Anno. D. T. Taday D. T. Ta	Annual priorition Arrences, p. 544.4 to reconstruct of other man and Arrences, p. 544.4 Ritor, p. 544.4 Ritor, p. 544.4 Ritor, p. 544.4 Ritor, p. 544.4 Ritor, p. 544.4 Ritor, p.	Gauge Y To Sales C Sales Anad F Sale H, p. SALARA RAA RAA Sa DUCTION SFRC) and months outside fibe or SFRC) and months outside fibe or sales of ap-
Carlo E Barge 1:* The preser stree of devisioners of the properties over devision the street weight and properties over devised applements are street deplements are street deplements are street the street how devised and the street properties the street and street properties and the street properties and th	City practice for file for a monoid lack of our presents and a mean marks then any present and are a monoid to any area monoid to area monoid to area a monoid and a present and a prese	T. Randiciam D. T. Taday Anto- consult 33-6486 3-54867 to 40 3-54867 to 40 3-54867 to 40 3-54867 to 40 3-54867 to 40 3-54867 to 40 3-54867 to 40 4-55864 to 40 4-55864 to 40 4-55864 to 40 4-55864 to 40 5686 to 40 4-55864 to 40 5686 to 40 56	Annual phoneses, p. 544, 4 Arrences, p. 544, 4 a	Gauge Y To Arter C Salen Anad F Sale M, p. 544.4R-8 R-54. Sec 7 DUCTION SPRC and monter of discontinuous fractional monter of discontinuous in figure poor. These a first types of ap-
Carlo & Bange, Is* The present state of development of the properties over discussed, a despineties opplements are discussed, a despineties opplements are discussed, a developments opplements are impaired, and then any, investes team banks, and CONTENTS CONTENTS CONTENTS 2.4 Contentions 3.4 Contents any 3.4 Contents are any 3.4 Contents are any opplements 3.4 Contents are any 3.4 Contents any 3.4 Contents are any opplements 3.4 Contents are any opplements and 3.4 Contents are any opplements are any opplements 3.4 Contents are any opplements and 3.4 Contents are any opplements are any opplements 3.4 Contents are any opplements are any opplements 3.4 Contents are any opplements are any opplements 4.4 Contents are any opplements are any opplements 4.4 Contents are any opplements are any opplements 3.4 Contents are any opplements are any opplements 3.4 Contents are any opplements are any opplements 3.4 Contents are any opplements 3.4 Contents are any opplements 4.4 Contents 4.4 Content	City practice for file for a monoid lack of our presents and a mean marks then any present and are a monoid to any area monoid to area monoid to area a monoid and a present and a prese	T. Randiciam D. T. Taday Anno. D. T. Taday D. T. Ta	Annual phoneses, p. 544, 4 Arrences, p. 544, 4 a	Gauge Y To Arter C Salen Anad F Sale M, p. 544.4R-8 R-54. Sec 7 DUCTION SPRC and monter of discontinuous fractional monter of discontinuous in figure poor. These a first types of ap-

Modern FRC Design

4 years of bipartisan efforts

- March 2014: Formation of a task group to rewrite document
- October 2016: sixth (final) draft was balloted
- March 2017: TAC meeting and approval
- October 2017: final changes and back to ACI
- Publication: 2018



Guide to Design with FRC

Scope of Document

This guide is intended for designers who are familiar with structural concrete containing conventional steel reinforcement, but who may need more guidance on the design and specification for FRC.

In this document, fibers are treated as reinforcement in concrete and not as admixture. The design guides in this document have been derived and verified for FRC with steel and synthetic macro fibers only.





Chapters 1 and 2

Introductions, Scope, Notations and Definitions

- Introduction and background for this document
- Basic information about fibers and FRC
- History of advancements in FRC
- Scope of the document and expectations
- Historical aspects on FRC studies (old 544.4R document)
- Definitions and notations used in the document



Chapter 3

Characteristics of FRC


- Classification of Fibers
- Mechanical Performance of FRC
- Standard Test Methods for FRC
- Strain Softening and Strain Hardening

Classification of fibers based on size (micro vs. macro) Classification of fibers based on type (steel vs. synthetic) ASTM requirements for each fiber type Applications and expectations for each fiber type













Crack control (bridging) in FRC beam under flexural loading


Standardized Testing of FRC

ASTM C1609






- Four point bending test
- Closed-loop control
- Typically strain-softening behavior



Chapter 4


Design Concepts and Guides

- Design Concepts
- Tensile Stress-Strain Response for FRC
- Correlation of Tensile and Flexural Response for FRC
- Design of RC for Flexure (Stress Block)
- Design of FRC for Flexure ASTM C1609/C1609M
- Design of FRC for Flexure Model Code 2010
- Design of FRC for Flexure Hybrid Reinforcement
- Design of FRC for Shear
- Parametric Based Design for FRC



Engineered Solutions

Parametric Based Design for FRC and Solved Example



Material model for singly reinforced concrete design

Chapter 5

Design for Specific Applications

- Slabs-on-Ground
- Extended Joint Spacing
- Elevated Floors/Slabs on Pile
- Composite Steel Decks
- Precast Units
- Shotcrete
- Crack Control and Durability





Slabs on Ground

Interior and exterior construction




FRC slabs using low shrinkage concrete and extended joint spacing





Why not mesh or bars?

- If placed too low, it doesn't work!
- If placed too high, it will be exposed!
- Always corrosion issue (deicing salts)!





Shotcrete

Moment design and crack control





- Repair work
- Slope stabilization
- Swimming pool construction
- Underground support



Chapter 6

Construction Practices

- Mix Design Recommendations for FRC
- Workability of FRC
- Adding and Mixing Fibers
- Placing, Consolidation and Finishing FRC
- Quality Control for FRC
- Contraction (Control) Joints
- Specifying FRC



tates' Materials Engineers Association

Adding and Mixing Fibers Different methods, different costs



Considerations – speed, costs, safety, fiber type, job site, specifications




Placing, Consolidating and Finishing FRC

Same as conventional concrete



FRC can be finished with similar tools as used for unreinforced concrete.



Davis Monthan AFB Tucson





Port of Long Beach



Specifying FRC

Summary of Fiber Reinforcement Tests & Parameters

	Reinforcement Purpose				
	Shrinkage/Temperature Crack Control	Post-Crack Tensile/Flexural Capacity			
Fiber Type	Synthetic microfiber Steel and synthetic macrofiber	Steel and synthetic macrofiber			
Test Method	ASTM C1579 or ASTM C1581*	ASTM C1609 or ASTM C1550 **			
Test / Spec Parameter	% in crack width reduction	Flexural residual strength or toughness			

* Prescriptive (dosage based) language may be used instead.

** Equivalent BS tests are EN 14651 and EN 14488



Several CALTRANS new/repair projects for bridge decks using synthetic fibers + SRA

(Cl, July 2013)

fibers. Deck-on-deck construction is especially prone to cracking due to drying shrinkage stresses. Relying upon our earlier experience of using SRAs to reduce early-age deck cracking and several previous successful applications of synthetic polyolefin macrofibers to restrain plastic and drying shrinkage cracking, the two technologies were combined for a "crackless" concrete deck (771 lb/yd3 [8.2 sacks or 457 kg/m3] of cement, 6% air, w/c of 0.51, SRA at 0.75 to 1.5 gal./yd3 [3.7 to 7.4 L/m3], and fibers at 3 lb/yd3 [1.8 kg/m3]). After 5 years of service, sections of the deck comprising both SRA and fibers exhibited very limited cracking. Cores taken at cracked locations indicated that cracks were very thin and most were arrested near the surface. Two cores extracted at full-depth (4 in. [102 mm]) crack locations showed finelined cracks kept intact by the fibers. In contrast, the control sections of the deck, placed without SRA and without fibers, exhibited substantial cracking within 6 weeks.

In 2011, a 5 in. (127 mm) "crack-free" deck was placed on



Fig. 6: Cast-in-place decks and spliced precast bulb-T girders on I-80 near Truckee, CA: (a) deck constructed without SRA; and (b) deck constructed with SRA (photos courtesy of Ric Maggenti)

ABC's of CRACK-Less Bridge Decks

With Applications in

ACCELERATED

BRIDGE CONSTRUCTION

Sonny Fereira, PE California Department of Transportation March 21, 2014 Bridge Contractors/ Caltrans Liaison Committee Meeting

Formula for the CRACK-Less Bridge Deck

A. Shrinkage Reducing Admixture*

B. Water Reducing Admixture*



*add to concrete mix

The Current Cost Of DoingBusiness v. CRACK-Less Deck\$50 MILLION TO SEAL
CRACKS\$2 MILLION FOR
CRACK-Less DECKS



	02
	02
5	6
Caltra	ns
STATE OF CAL	LIFORNIA
DEPARTMENT OF TR	ANSPORTATION
NOTICE TO B	
	DDERS
AND	
SPECIAL PRO	OVISIONS
SPECIAL PRO FOR CONSTRUCTION ON STATE HIGHWA SEIAD VALLEY AT VARIOUS LOCATIO THOMPSON CREEK BRIDGE TO 0.2 MILE E	AY IN SISKIYOU COUNTY NEAR DNS FROM 0.1 MILE WEST OF
FOR CONSTRUCTION ON STATE HIGHWA SEIAD VALLEY AT VARIOUS LOCATIO	AY IN SISKIYOU COUNTY NEAR DNS FROM 0.1 MILE WEST OF EAST OF BEAVER CREEK BRIDGE
FOR CONSTRUCTION ON STATE HIGHWA SEIAD VALLEY AT VARIOUS LOCATIO THOMPSON CREEK BRIDGE TO 0.2 MILE E	AY IN SISKIYOU COUNTY NEAR DNS FROM 0.1 MILE WEST OF EAST OF BEAVER CREEK BRIDGE
FOR CONSTRUCTION ON STATE HIGHWA SEIAD VALLEY AT VARIOUS LOCATIO THOMPSON CREEK BRIDGE TO 0.2 MILE E In District 02 On F Under	AY IN SISKIYOU COUNTY NEAR DNS FROM 0.1 MILE WEST OF EAST OF BEAVER CREEK BRIDGE
FOR CONSTRUCTION ON STATE HIGHWA SEIAD VALLEY AT VARIOUS LOCATIO THOMPSON CREEK BRIDGE TO 0.2 MILE E In District 02 On F Under	AY IN SISKIYOU COUNTY NEAR ONS FROM 0.1 MILE WEST OF EAST OF BEAVER CREEK BRIDGE Route 96
FOR CONSTRUCTION ON STATE HIGHW, SEIAD VALLEY AT VARIOUS LOCATIO THOMPSON CREEK BRIDGE TO 0.2 MILE E In District 02 On F Under Bid book dated September 26, 2016 Project plans approved June 15, 2016 Identified by	AY IN SISKIYOU COUNTY NEAR DNS FROM 0.1 MILE WEST OF EAST OF BEAVER CREEK BRIDGE Route 96 Standard Specifications dated 2010 Standard Plans dated 2010
FOR CONSTRUCTION ON STATE HIGHW, SEIAD VALLEY AT VARIOUS LOCATIO THOMPSON CREEK BRIDGE TO 0.2 MILE E In District 02 On F Under Bid book dated September 26, 2016 Project plans approved June 15, 2016 Identified by Contract No. 02-4	AY IN SISKIYOU COUNTY NEAR DNS FROM 0.1 MILE WEST OF EAST OF BEAVER CREEK BRIDGE Route 96 Standard Specifications dated 2010 Standard Plans dated 2010 Y 4E6504
FOR CONSTRUCTION ON STATE HIGHW, SEIAD VALLEY AT VARIOUS LOCATIO THOMPSON CREEK BRIDGE TO 0.2 MILE E In District 02 On F Under Bid book dated September 26, 2016 Project plans approved June 15, 2016 Identified by Contract No. 02-4 02-Sis-96-R52.5	AY IN SISKIYOU COUNTY NEAR DNS FROM 0.1 MILE WEST OF EAST OF BEAVER CREEK BRIDGE Route 96 Standard Specifications dated 2010 Standard Plans dated 2010 y 4E6504 5/88.4
FOR CONSTRUCTION ON STATE HIGHW, SEIAD VALLEY AT VARIOUS LOCATIO THOMPSON CREEK BRIDGE TO 0.2 MILE E In District 02 On F Under Bid book dated September 26, 2016 Project plans approved June 15, 2016 Identified by Contract No. 02-4	AY IN SISKIYOU COUNTY NEAR DNS FROM 0.1 MILE WEST OF EAST OF BEAVER CREEK BRIDGE Route 96 Standard Specifications dated 2010 Standard Plans dated 2010 y 4E6504 5/88.4
FOR CONSTRUCTION ON STATE HIGHW, SEIAD VALLEY AT VARIOUS LOCATIO THOMPSON CREEK BRIDGE TO 0.2 MILE E In District 02 On F Under Bid book dated September 26, 2016 Project plans approved June 15, 2016 Identified by Contract No. 02-4 02-Sis-96-R52.5	AY IN SISKIYOU COUNTY NEAR DNS FROM 0.1 MILE WEST OF EAST OF BEAVER CREEK BRIDGE Route 96 Standard Specifications dated 2010 Standard Plans dated 2010 y 4E6504 5/88.4 100012
FOR CONSTRUCTION ON STATE HIGHW, SEIAD VALLEY AT VARIOUS LOCATIO THOMPSON CREEK BRIDGE TO 0.2 MILE E In District 02 On F Under Bid book dated September 26, 2016 Project plans approved June 15, 2016 Identified by Contract No. 02-4 02-Sis-96-R52.5 Project ID 021200 Federal-Aid Pro ACST-P096(06	AY IN SISKIYOU COUNTY NEAR DNS FROM 0.1 MILE WEST OF EAST OF BEAVER CREEK BRIDGE Route 96 Standard Specifications dated 2010 Standard Plans dated 2010 y 4E6504 5/88.4 00012 oject 50)E
FOR CONSTRUCTION ON STATE HIGHW, SEIAD VALLEY AT VARIOUS LOCATIO THOMPSON CREEK BRIDGE TO 0.2 MILE E In District 02 On F Under Bid book dated September 26, 2016 Project plans approved June 15, 2016 Identified by Contract No. 02-4 02-Sis-96-R52.5 Project ID 021200 Federal-Aid Pro	AY IN SISKIYOU COUNTY NEAR DNS FROM 0.1 MILE WEST OF EAST OF BEAVER CREEK BRIDGE Route 96 Standard Specifications dated 2010 Standard Plans dated 2010 y 4E6504 5/88.4 00012 oject 50)E
FOR CONSTRUCTION ON STATE HIGHW, SEIAD VALLEY AT VARIOUS LOCATIO THOMPSON CREEK BRIDGE TO 0.2 MILE E In District 02 On F Under Bid book dated September 26, 2016 Project plans approved June 15, 2016 Identified by Contract No. 02-4 02-Sis-96-R52.5 Project ID 021200 Federal-Aid Pro ACST-P096(06	AY IN SISKIYOU COUNTY NEAR DNS FROM 0.1 MILE WEST OF EAST OF BEAVER CREEK BRIDGE Route 96 Standard Specifications dated 2010 Standard Plans dated 2010 y 4E6504 5/88.4 000012 oject 50)E g Contract
FOR CONSTRUCTION ON STATE HIGHW, SEIAD VALLEY AT VARIOUS LOCATIO THOMPSON CREEK BRIDGE TO 0.2 MILE E In District 02 On F Under Bid book dated September 26, 2016 Project plans approved June 15, 2016 Identified by Contract No. 02-4 02-Sis-96-R52.5 Project ID 021200 Federal-Aid Pro ACST-P096(06	AY IN SISKIYOU COUNTY NEAR DNS FROM 0.1 MILE WEST OF EAST OF BEAVER CREEK BRIDGE Route 96 Standard Specifications dated 2010 Standard Plans dated 2010 y 4E6504 5/88.4 000012 oject 50)E

51 CONCRETE STRUCTURES

Add to section 51-1.01C(1):

If the methacrylate crack treatment is performed within 100 feet of a residence, business, or public space, submit a public safety plan that includes the following:

- Public notification letter with a list of delivery and posting addresses. The letter must describe the work to be performed and state the treatment work locations, dates, and times. Deliver the letter to residences and businesses within 100 feet of overlay work and to local fire and police officials not less than 7 days before starting overlay activities. Post the letter at the job site.
- Airborne emissions monitoring plan. A CIH certified in comprehensive practice by the American Board of Industrial Hygiene must prepare and execute the plan. The plan must have at least 4 monitoring points including the mixing point, application point, and point of nearest public contact. Monitor airborne emissions during overlay activities.
- 3. Action plan for protecting the public if levels of airborne emissions exceed permissible levels.
- 4. Copy of the CIH's certification.

After completing methacrylate crack treatment activities, submit results from monitoring production airborne emissions as an informational submittal.

Replace the 2nd paragraph of section 51-1.01C(1) with:

Submit a deck placement plan for concrete bridge decks. Include in the placement plan your method and equipment for ensuring that the concrete bridge deck is kept damp by misting immediately after finishing the concrete surface.

Add to section 51-1.02B:

For the portions of structures shown in the following table, concrete must contain at least 675 pounds of cementitious material per cubic yard:

Bridge name and no.	Portion of structure		
Thompson Creek Bridge (Bridge no. 02-0068)	All except footings and piles		
Seiad Creek Bridge (Bridge no. 02-0072)	All except footings and piles		
Beaver Creek Bridge (Bridge no. 02-0081)	All except footings and piles		

Concrete for concrete bridge decks must contain polymer fibers. Each cubic yard of concrete must contain at least 1 pound of microfibers and at least 3 pounds of macrofibers.

Concrete for concrete bridge decks must contain a shrinkage reducing chemical admixture. Each cubic yard of concrete must contain at least 3/4 gallon of a shrinkage reducing admixture. If you use the maximum dosage rate shown on the Authorized Material List for the shrinkage reducing admixture, your submitted shrinkage test data does not need to meet the shrinkage limitation specified.

Delete the 2nd sentence of the 1st paragraph of section 51-1.03E(5).

Contract No. 02-4E6504 61

CALTRANS spec: 1 lb/yd³ micro and 3 lb/yd³ macro fibers ³/₄ gal SRA (0.032% shrinkage)




Task 1 – Laboratory Material Testing

B – stands for Blended Aggregate FR – stands for Fibers



Mix Designs with Macro Fibers

Mix ID	Class	НРС	HPC-	FR-	FR-
(lb/cy)	Α	TIFC	В	HPC	HPC-B
Cement,	658	520	520	520	520
Туре І					
Fly Ash,	-	130	130	130	130
Class C					
Silica Fume	-	25	25	25	25
Total	658	675	675	675	675
Cement					
w/b ratio	0.410	0.38	0.38	0.382	0.382
		2	2		
#57	1,800	1,80	1,50	1,800	1,500
		0	0		
#8	-	-	300	-	300
Sand	1,205	1,11	1,11	1,113	1,113
		3	3		
HRWR	2.0	2.5	2.0	2.5	3.5
(oz/cwt)					
AEA	1.0	1.0	1.0	1.0	1.0
(oz/cwt)					
Macro Fibs	-	-	-	PPF	PPF 5lb
(lb/cy)				5lb	
Slump (in.)	7	8	4	6	6.5
Air (%)	5.5	-	-	8.5	7



0% Load →

90% Load →

100% Load → Duct

Ductile Failure






Task 2 – Analysis of Laboratory Testing Results




Shrinkage and Cracking Performance



Macro Polypropylene Fibers (added to HPC) reduced:

- Free Shrinkage: 27% (w/HPC) & 46% (Class A)
- Cracking Area: up to 22% (HPC) & 73% (Class A)
- Max. Crack Width: up to 12% (HPC) & 35% (Class A)



Task 3 – Mock-up Slab

Field Validation

- A mock-up slab was cast to validate the applicability of the proposed FR-HPC mixture prior to casting the actual bridge decks
- The concrete **passed** the slump and air test.
- No issues were found during mixing, pumping, casting and finishing the concrete.







Task 4 – Field Implementation

Field Implementation and Testing

- FR-HPC was successfully implemented on the major highway bridge deck replacement in NJ.
- Field Crack Mapping (3 field trips in 300 days) show that FR-HPC reduces number of cracks by 5.3%, narrower mean crack width by 28.6%, and lower cracking area by 33.3%, compared to HPC.
- Another crack map will be performed one year after opening to traffic.
- A technical **specification** is prepared.







ACKNOWLEDGEMENT



The financial support and technical information from various research projects sponsored by the Research on Concrete Application for Sustainable Transportation (RE-CAST), Tier 1 University Transportation Center (UTC) at Missouri University of Science and Technology, and the New Jersey Turnpike Authority (NJTA) are greatly appreciated. Hani Nassif, PE, PhD, FACI, Professor and Director Adi Abu-Obeidah, PhD, Research Associate Chaekuk Na, PhD, Research Associate Rutgers Infrastructure Monitoring and Evaluation (RIME) Group



Questions, Comments, Discussion?

Bill Lyons FACI National Business Development Group – Northeast Region 201-401-3391 wlyons@euclidchemical.com



Materials Engineers Association