



Ground Penetrating Radar Pavement Density Validation

Rick Bradbury, Maine Department of Transportation

NESMEA

Newark, Delaware

October 18, 2016



U.S. Department of Transportation
Federal Highway Administration




MaineDOT

AMERICAN ASSOCIATION
OF STATE HIGHWAY AND
TRANSPORTATION OFFICIALS
AASHTO

Presentation Overview

- Maine's need for improved asphalt evaluation
- Testing of Ground Penetrating Radar technology
- Interim results
- Next steps



Maine's Transportation Needs



- Concern about quality of asphalt pavement construction
- Between 4,000 – 12,000 tons of pavement replaced annually due to defects
- Substandard practices cannot always be identified with current random sampling
- Tool needed to improve consistency of laydown practices







18 11:37 AM

Quality Characteristics



- Smoothness
 - Easily measured with current technologies
- In-place density
 - Density gauges or core samples
 - Random sampling; not complete evaluation
- Surface uniformity (seldom measured)
 - Difficult to measure with current methods

Rapid Technologies to Enhance Quality Control on Asphalt Pavements (R06C)


Two non-destructive techniques for evaluating asphalt pavements during construction

- Infrared thermal scanning
- Ground Penetrating Radar
- Measures uniformity and potential defect areas in asphalt pavements during construction.
- Offers real-time testing of potentially 100 percent of the pavement area.

SHRP2 Solution - GPR

Rapid Technologies to Enhance Quality Control on Asphalt Pavements (R06C)

- GPR technology provides density data over a greater area
- Can identify areas of low density quickly
- Potential to provide better information for QC and Acceptance



Early Efforts with GPR

NCHRP IDEA Project 61 – “Development of a Portable Pavement Thickness/Density Meter”

- Goal – portable GPR device to measure thickness & density in real time
- Help achieve more uniform pavement layers
- Tried several GPR configurations on various test sites – correlated to cores
 - Thickness showed strong correlation
 - Density correlation not as strong

Early Efforts with GPR



Early Efforts with GPR



SHRP2 R06C research - GPR

- Built upon past work – focused on density, not thickness
 - Texas Transportation Institute
 - Finland
- New device measures surface dielectric
- Software correlates dielectric value to air voids

SHRP2 Validation Project research team:

Lev Khazanovich and Ryan Conway

Department of Civil, Environmental, and Geo-Engineering

University of Minnesota

Technical assistance from GSSI

Prototype Rolling Density Meter

- Provides direct readout of density – no post-processing
- Lightweight, portable
- Can be used on thin layers
 - TxDOT 1/2" overlays
- Needs further validation



Courtesy of TTI


GSSI PaveScan RDM



GSSI PaveScan RDM



Density Profiles



ADJACENT TO EDGE OF PAVEMENT

Calibration Procedure

- Scan a pavement section
- Device identifies high, low, median density locations
- Take static reading directly over each location
- Obtain cores for correlation




Calibration Procedure



First project


- 4 miles
- 1-1/4" Overlay
- 9.5mm HMA




Correlation results

GPR LOCATION	CORE RESULT (% Gmm)
HIGH	95.9
HIGH	96.0
LOW	91.5
LOW	90.4
MEDIAN	93.6
Average Core Density	93.5%
Acceptance Cores	95.6, 91.7, 93.2
Average	93.5%

Regression Analysis




Density Profiles



ADJACENT TO CENTERLINE JOINT

Density Profiles



WHEEL PATH PROFILE

Survey Results

In-Place Air Voids			
	Average	Max.	Std.
Outside Edge	6.22	14.60	1.11
Joint	6.32	18.63	1.12
Wheel Path	5.03	5.92	0.14

Additional Projects

- Project 2
 - 16 miles, I – 95
 - 1-1/2" Mill & Fill
 - 12.5mm HMA
- Project 3
 - 4.5 miles
 - 3/4" Overlay
 - 9.5mm HMA
- Work still underway – Calibration correlation not available at this time

Desired Short-term Benefits



- More uniformly constructed hot- and warm-mix asphalt layers
- Better in-place field density
- Improved communication among paving crews, QC, and DOT personnel
- Improved ride
- Less reliance on visual inspection
- Reduced discrepancies between contractor and agency test data

Long-Term Goals

- Better inspection coverage to avoid noncompliance penalties.
- Smoother, longer-lasting pavements.
- Reduced need for corrective action due to low-density asphalt pavements.
- Reduced construction time; fewer incidents of replacing new pavement.
- Lessen exposure of workers and public to work zone hazards.

Next Steps

- Additional validation work in 2017
- Evaluate various applications:
 - Thin overlays
 - Different Mix types
- Portability of calibration
- Ruggedness testing

Next Steps

- Determine best use for device:
 - QC, Acceptance, both?
- Contractor education
- Demonstration projects
- Specification development

For more information

For more information on improving the quality of your asphalt pavements through SHRP2 products contact:

- Steve Cooper (FHWA) stephen.j.cooper@dot.gov
- Evan Rothblatt (AASHTO) erothblatt@aaashto.org

For more information on Maine's experience, contact:

- Rick Bradbury (Maine DOT)
Richard.Bradbury@maine.gov



MaineDOT

Integrity – Competence - Service